## APPLICATION FOR PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF NEVADA NEW PRIORITY DATE:

Date of filing in State Engineer's Office	MAR 2 8 1988 MAR 17 2010	
Returned to applicant for correction	APR 7 1988	
Corrected application filed	APR 1 8 1988	
Map filed	APR 1 8 1988	
• •	Trustee	
•	e No. 1, of Las Vegas,	
Nevada 89104 State and Zip Code No.	, hereby make application for permission to appropriate the public	
	ted. (If applicant is a corporation, give date and place of incorporation; if a	
copartnership or association, give names of m	embers.)N/A	
1. The source of the proposed appropriation	is from an underground source.  Name of stream, lake, spring, underground or other source	
2. The amount of water applied for is	.062 c.f.s. second-feet One second-foot equals 448.83 gals. per min.	
(a) If stored in reservoir give number of a	icre-feet N/A	
3. The water to be used forQua	si-Municipal purposes ation, power, mining, manufacturing, domestic, or other use. Must limit to one use.	
4. If use is for:		
(a) Irrigation, state number of acres to be	irrigatedN/A	
(b) Stockwater, state number and kinds of	animals to be watered N/A	
(c) Other use (describe fully under "No.	12. Remarks") ( See Item No. 12 )	
(d) Power:		
(1) Horsepower developed	N/A	
(2) Point of return of water to stream.	N/A	
Section 27, Township 19 Sou survey, and by course and distance to a section corner. If of	e at the following point within the Southwest one-quarter -quarter (NE <sup>1</sup> / <sub>4</sub> ) of Describe as being within a 40-acre subdivision of public th, Range 60 East, MDBM from which the center on unsurveyed land, it should be so stated one-quarter (C <sup>1</sup> / <sub>4</sub> ) of said 29'15" West a distance of 1328.71.	
6. Place of use Lots 25,26,27,28	, 29, 42, 43, 44, 45 and 46 of Block 2, Tropical be by legal subdivision. If on unsurveyed land, it should be so stated.	
	in Book 3, page 98 of Plats, Clark County,	
Ne <u>vada Official Records, w</u>	ithin the Southwest quarter (SW½) of the	
Northeast quarter (NE1) of	Section 27, Township 19 South, Range 60	
East, MDBM.		
7. Use will begin about January 1  Month and Day	st. and end about December 31st., of each year.	
·	the provisions of NRS 535.010 you may be required to submit plans and	
specifications of your diversion or storage	e works.) Drill 8" steel cased well, install State manner in which water is to be diverted, i.e. diversion structure, ditches and	
	ping, storage tank and pressure tank.	
9. Estimated cost of works \$15,0	00.00 -	

Estimated time required to construct works	1 year  If well completed, describe works.
Estimated time required to complete the application	n of water to beneficial use 3 to 5 years.
	watering, state number and type of units to be served or annual
Well to service 10 houses	
ompared jm/bk pm/se	S/Judy Dawson, Trustee Judy Dawson, Trustee (Applicate By AGENT: Robert Fulster No. 639 940 So. Highland Dr. Las Vegas, Nevada 89106
rotested	
APPROVAL	OF STATE ENGINEER
This is to certify that I have examined the foregoing a mitations and conditions:	application, and do hereby grant the same, subject to the following
	to existing rights and is further subject to
district or a municipality engaged if be installed and maintained in diversion and accurate measurement use. The totalizing meter must be before the Proof of Completion or right must allow for a reasonable I shall be equipped with a 2-inch of well is flowing, a valve must be the total total times. This source is located within an art to NRS 534.030. The State retains herein granted at any and all times. This Permit does not extend to on public, private or corporate land the issuance of this permit does the permit holder obtain other agencies.	an be furnished by an entity such as a water in furnishing water. A totalizing meter must the discharge pipeline near the point of ints must be kept of water place to beneficial installed before any use of water begins, or of Work is filed. It is understood that this lowering of the static water level. The well opening for measuring depth to water. If the oe installed and maintained to prevent waste. The designated by the State Engineer pursuant in the right to regulate the use of the water the permittee the right of ingress and egress
district or a municipality engaged is be installed and maintained in diversion and accurate measurement use. The totalizing meter must be before the Proof of Completion or right must allow for a reasonable I shall be equipped with a 2-inch of well is flowing, a valve must be the total transfer of the State retains the total transfer of the permit does not extend to the permit does of this permit does the permit does of the permit does not extend the permit holder obtain other agencies.  The issuance of this permit does not extend the permit holder obtain other agencies.	an be furnished by an entity such as a water in furnishing water. A totalizing meter must the discharge pipeline near the point of ints must be kept of water place to beneficial installed before any use of water begins, or of Work is filed. It is understood that this lowering of the static water level. The well opening for measuring depth to water. If the oe installed and maintained to prevent waste, rea designated by the State Engineer pursuant ins the right to regulate the use of the water the permittee the right of ingress and egress ds.  es not waive the requirements that remaining the permits from State, Federal and local
district or a municipality engaged is be installed and maintained in diversion and accurate measurement use. The totalizing meter must be before the Proof of Completion or right must allow for a reasonable I shall be equipped with a 2-inch of well is flowing, a valve must be the total transfer of the source is located within an art to NRS 534.030. The State retains herein granted at any and all times.  This Permit does not extend to on public, private or corporate land the permit holder obtain other agencies.  The issuance of this permit does not extend to a million gallone aroundly.	an be furnished by an entity such as a water in furnishing water. A totalizing meter must the discharge pipeline near the point of ints must be kept of water place to beneficial installed before any use of water begins, or of Work is filed. It is understood that this lowering of the static water level. The well opening for measuring depth to water. If the oe installed and maintained to prevent waste, rea designated by the State Engineer pursuant ins the right to regulate the use of the water the permittee the right of ingress and egress ds.  es not waive the requirements that repermits from State, Federal and local to the amount which can be applied to beneficial use, and not to
district or a municipality engaged is be installed and maintained in diversion and accurate measurement use. The totalizing meter must be before the Proof of Completion or right must allow for a reasonable I shall be equipped with a 2-inch of well is flowing, a valve must be the total total times. This source is located within an art to NRS 534.030. The State retains herein granted at any and all times. This Permit does not extend to on public, private or corporate land the issuance of this permit does the permit holder obtain other agencies.  The issuance of this permit does amount of water to be appropriated shall be limited to the million gallons annually.  The issuance of this permit does not extend the permit holder obtain other agencies.  The issuance of this permit does the permit holder obtain other agencies.  The issuance of this permit does not extend the permit holder obtain other agencies.  The issuance of this permit does not extend the permit holder obtain other agencies.  The issuance of this permit does not extend the permit holder obtain other agencies.  The issuance of this permit does not extend the permit holder obtain other agencies.  The issuance of this permit does not extend the permit holder obtain other agencies.	an be furnished by an entity such as a water in furnishing water. A totalizing meter must the discharge pipeline near the point of ints must be kept of water place to beneficial installed before any use of water begins, or of Work is filed. It is understood that this lowering of the static water level. The well opening for measuring depth to water. If the oe installed and maintained to prevent waste. The readesignated by the State Engineer pursuant in the right to regulate the use of the water in the permittee the right of ingress and egress is.  The permittee the requirements that the permits from State, Federal and local is to the amount which can be applied to beneficial use, and not to be feet per second, but not to exceed 3.65
district or a municipality engaged is be installed and maintained in diversion and accurate measurement use. The totalizing meter must be before the Proof of Completion or right must allow for a reasonable I shall be equipped with a 2-inch of well is flowing, a valve must in this source is located within an art to NRS 534.030. The State retains herein granted at any and all times.  This Permit does not extend to on public, private or corporate land. The issuance of this permit does the permit holder obtain other agencies.  The amount of water to be appropriated shall be limited used.  O.062  Cut million gallons annually.  Ork must be prosecuted with reasonable diligence and coof of completion of work shall be filed on or before.	an be furnished by an entity such as a water in furnishing water. A totalizing meter must the discharge pipeline near the point of ints must be kept of water place to beneficial installed before any use of water begins, or of Work is filed. It is understood that this lowering of the static water level. The well opening for measuring depth to water. If the oe installed and maintained to prevent wasterea designated by the State Engineer pursuant in the right to regulate the use of the water the permittee the right of ingress and egress is.  The permittee the requirements that the permittee the requirements that the permittee from State, Federal and local to the amount which can be applied to beneficial use, and not to bic feet per second but not to exceed 3.65  November 12, 1990
district or a municipality engaged is be installed and maintained in diversion and accurate measurement use. The totalizing meter must be before the Proof of Completion or right must allow for a reasonable I shall be equipped with a 2-inch of well is flowing, a valve must in the total to	an be furnished by an entity such as a water in furnishing water. A totalizing meter must the discharge pipeline near the point of ints must be kept of water place to beneficial installed before any use of water begins, or of Work is filed. It is understood that this lowering of the static water level. The well opening for measuring depth to water. If the oe installed and maintained to prevent waste, rea designated by the State Engineer pursuant instable to regulate the use of the water of the permittee the right of ingress and egress disces not waive the requirements that it is permits from State, Federal and local to the amount which can be applied to beneficial use, and not to bic feet per second, but not to exceed 3.65  November 12, 1990  November 12, 1990  October 12, 1993
district or a municipality engaged is be installed and maintained in diversion and accurate measurement use. The totalizing meter must be before the Proof of Completion or right must allow for a reasonable I shall be equipped with a 2-inch owell is flowing, a valve must be the total tota	an be furnished by an entity such as a water in furnishing water. A totalizing meter must the discharge pipeline near the point of ints must be kept of water place to beneficial installed before any use of water begins, or of Work is filed. It is understood that this lowering of the static water level. The well opening for measuring depth to water. If the oe installed and maintained to prevent waste, rea designated by the State Engineer pursuant in the right to regulate the use of the water is the permittee the right of ingress and egress dis.  The permittee the requirements that is not waive the requirements that is permits from State, Federal and local is to the amount which can be applied to beneficial use, and not to be be completed on or before.  October 12, 1990  November 12, 1993  De filed on or before.  November 12, 1993
district or a municipality engaged is be installed and maintained in diversion and accurate measurement use. The totalizing meter must be before the Proof of Completion or right must allow for a reasonable I shall be equipped with a 2-inch of well is flowing, a valve must in this source is located within an art to NRS 534.030. The State retains herein granted at any and all times.  This Permit does not extend to on public, private or corporate land.  The issuance of this permit does the permit holder obtain other agencies.  The amount of water to be appropriated shall be limited ceed	an be furnished by an entity such as a water in furnishing water. A totalizing meter must the discharge pipeline near the point of ints must be kept of water place to beneficial installed before any use of water begins, or of Work is filed. It is understood that this lowering of the static water level. The well opening for measuring depth to water. If the one installed and maintained to prevent waste. The readesignated by the State Engineer pursuant in the right to regulate the use of the water is the permittee the right of ingress and egress is.  The permittee the requirements that is not waive the requirements that is permits from State, Federal and local is to the amount which can be applied to beneficial use, and not to be feet per second. The but not to exceed 3.65  November 12, 1990  October 12, 1993  be filed on or before
district or a municipality engaged is be installed and maintained in diversion and accurate measurement use. The totalizing meter must be before the Proof of Completion or right must allow for a reasonable I shall be equipped with a 2-inch or well is flowing, a valve must be the total source is located within an art to NRS 534.030. The State retains herein granted at any and all times.  This Permit does not extend to on public, private or corporate land. The issuance of this permit does the permit holder obtain other agencies.  The amount of water to be appropriated shall be limited used.  The insulance of this permit does the permit holder obtain other agencies.  The amount of water to be appropriated shall be limited used.  The insulance of this permit does not conform the process of the proposition of water to be appropriated shall be limited used.  The insulance of this permit does not conform the process of the proces	an be furnished by an entity such as a water in furnishing water. A totalizing meter must the discharge pipeline near the point of ints must be kept of water place to beneficial installed before any use of water begins, or of Work is filed. It is understood that this lowering of the static water level. The well opening for measuring depth to water. If the oe installed and maintained to prevent waste, rea designated by the State Engineer pursuant in the right to regulate the use of the water is the permittee the right of ingress and egress dis.  The permittee the requirements that is not waive the requirements that is permits from State, Federal and local is to the amount which can be applied to beneficial use, and not to be be completed on or before.  October 12, 1990  November 12, 1993  De filed on or before.  November 12, 1993
district or a municipality engaged is be installed and maintained in diversion and accurate measurement use. The totalizing meter must be before the Proof of Completion or right must allow for a reasonable I shall be equipped with a 2-inch of well is flowing, a valve must be to NRS 534.030. The State retains herein granted at any and all times. This Permit does not extend to on public, private or corporate land. The issuance of this permit does the permit holder obtain other agencies.  The amount of water to be appropriated shall be limited acced.  O.062  willion gallons annually.  Town must be prosecuted with reasonable diligence and to of completion of work shall be filed on or before. The application of water to beneficial use shall be filed on or before. The publication of water to beneficial use shall be filed on the permit of the application of water to beneficial use shall be filed on the permit of the application of water to beneficial use shall be filed on the permit of the application of water to beneficial use shall be filed on the permit of the application of water to beneficial use shall be filed on the permit of the application of water to beneficial use shall be filed on the permit of t	an be furnished by an entity such as a water in furnishing water. A totalizing meter must the discharge pipeline near the point of ints must be kept of water place to beneficial installed before any use of water begins, or of Work is filed. It is understood that this lowering of the static water level. The well opening for measuring depth to water. If the one installed and maintained to prevent waste. The rea designated by the State Engineer pursuant that the right to regulate the use of the water of the permittee the right of ingress and egress discharges and waive the requirements that the permits from State, Federal and local to the amount which can be applied to beneficial use, and not to bic feet per second. But not to exceed 3.65  November 12, 1990  October 12, 1993  be filed on or before
district or a municipality engaged is be installed and maintained in diversion and accurate measurement use. The totalizing meter must be before the Proof of Completion or right must allow for a reasonable I shall be equipped with a 2-inch of well is flowing, a valve must in the source is located within an art to NRS 534.030. The State retains herein granted at any and all times.  This Permit does not extend to on public, private or corporate land. The issuance of this permit does the permit holder obtain other agencies. The amount of water to be appropriated shall be limited exceed	an be furnished by an entity such as a water in furnishing water. A totalizing meter must the discharge pipeline near the point of ints must be kept of water place to beneficial installed before any use of water begins, or of Work is filed. It is understood that this lowering of the static water level. The well opening for measuring depth to water. If the oe installed and maintained to prevent waste. The read designated by the State Engineer pursuant in the right to regulate the use of the water. The permittee the right of ingress and egress is.  The permittee the requirements that is not waive the requirements that is permits from State, Federal and local to the amount which can be applied to beneficial use, and not to bic feet per second. The but not to exceed 3.65  The completed on or before.  October 12, 1990  November 12, 1993  De filed on or before.  October 12, 1993  The permit of the more of the water is not waiter to exceed 3.65  November 12, 1993  The permit of the more of the water is not waiter to exceed 3.65  The permit of the more of the more of the water is not waiter to exceed 3.65  The permit of the more of the water is not waiter to exceed 3.65  The permit of the more of the more of the water of the water is not waiter to exceed 3.65  The permit of the province of the water of th

CANGELLED JAN 2 5 2010 BECAUSE OF FAILURE OF APPLICANT TO COMPLY WITH THE PROVISIONS OF PERMIT